

OPILED® Panel & Down Light



OPILED® Circle Panel Light					Unit Price	Picture
Specification	size		Wattage	Idr		
LED: SMD2835 Epistar	Inbow	4 inch(Ø 145*20mm) Hole size:128-132mm	8W	240,000		
Voltage: 100-240V		6 inch(Ø 180*20mm) Hole size: 163-170mm	11W	280,000		
Frequency: 50/60Hz		8 inch(Ø 240*20mm) Hole size: 218-225mm	14W	349,000		
Power Factor: >0,95						
Ambient temp: -20° ~ 40°	Outbow	6 inch ceiling(Ø 180*35mm),Surface installation	11W	325,000		
CCT : 3000K, 4000K, 6000K		8 inch ceiling(Ø 240*35mm),Surface installation	14W	393,000		
Lifetime 40.000 hours						
OPILED® Square Panel Light J series					Unit Price	Picture
Specification	size		Wattage	Idr		
LED: SMD4014	L*W*H ,300*300*9mm, 295*295*9mm		18W	532,000		
Voltage: 100-240V						
Frequency: 50/60Hz	L*W*H ,300*300*9mm, 295*295*9mm		24W	780,000		
Power Factor: >0,95						
Ambient temp: -20° ~ 40°	L*W*H ,600*600*9mm, 595*595*9mm		40W	920,000		
CCT : 3000K, 4000K, 6000K						
Efficacy 100 lumen / watt in 6000K	L*W*H ,300*1200*9mm, 395*1195*9mm		40W	940,000		
Lifetime 40.000 hours						
2 years warranty	L*W*H ,600*1200*9mm, 395*1195*9mm		55W	1,560,000		

Term of Payment : 30% DP, CODelivery Time: 45 days
 Price can be changed without notice.